BLUE OCEAN® Rugged Megaphone


SPECIFICATIONS

mpetitor

Three

mpetito

Two



AUDIO

Power Output Microphone Amplifier

BATTERY

Battery Pack Battery Charger

Battery Usage Life

Battery Cycle Life

PHYSICAL

Dimensions

Weight

Shell Material

ENVIRONMENTAL

Temperature Range Water Resistance Buoyancy Drop Resistance

22 watts peak 19 watts rated Dynamic Weatherproof Higher-efficiency Class-D digital amplifier

NK Blue Ocean Lithium-Polymer Battery Pack – NK# 0105 11.1VDC Typical, 11.1 Whr NK Blue Ocean Battery Charger – PN 0106 Input Voltage: 90-264VAC, 50-60Hz, 7 Watts Universal input capable – compatible with all world currents with appropriate adapter plug

Dependent upon volume and continuity of operation. 8 hours of typical operation – defined as speaking 35% of the time at volume level 6. 30 hours of standby time. 80% rate capacity after 300 charge/discharge cycles; 60% rated capacity after 500 charge /discharge cycles

INCLUDED

Blue Ocear

Megaphone

mpetito

One

Comparison of Speech Transmission Index measured at 93.5 feet

(diamond) and 186 feet (circle)

Megaphone Charger Battery Pack Strap Bumper

MISSION CRITICAL Accessories

Spare Battery- p/n 0105 External Microphone with Head Strap

Charging: 0°C to 45°C / 32°F to 115°F

Megaphone: 12.75 x 12 x 8.5 in / 31.75 x 30 x 21.25 cm

Megaphone: 3.4 lbs with battery pack installed

Battery Pack: 3 x 2 x 1.55

Polycarbonate

Battery Charger: 13.6 oz. / 385 gr Battery Pack: 3.8 oz. / 108 gr

Battery Charger: 2.5 x 4.25 x 32.5 in / 6.25 x 10.75 x 8.25 cm

IP-67 (Excludes all dust and water for 30 minutes at 3.3ft / 1M submersion) Megaphone with battery pack installed floats. Battery Pack alone and charger do not float. MIL-STD-810G 516.6 Procedure IV Transit Shock, drop height 36 in / 91 cm onto plywood over concrete.

Find Quality Products Online at:

www.GlobalTestSupply.com

sales@GlobalTestSupply.com