


# testo Smart Probe Thermo-hygrometer

testo 605i

Up To 350ft.  
Bluetooth Range!



Quickly and accurately measures relative humidity and temperature in rooms, ducts, and chambers

Automatically calculates dew point & wet bulb temperature


Probe now foldable to 90°

Bluetooth range of up to 350 feet

Small diameter probe is ideal for in-duct measurements

Tough, accurate, and easy-to-use

For all HVAC/R technicians and contractors



Bluetooth  
+ App

testo Smart Probes App  
for free download



\*Operates with iOS or Android smart devices such as smart phones, tablets, etc.

The testo 605i Smart Probe thermo-hygrometer is a humidity and temperature measuring instrument that quickly and accurately measures relative humidity, dew point, and temperature in rooms, ducts, registers, and environmental boxes/chambers. Users can read the measurements using the testo **Smart Probes App** installed on their smart device. Smart Probes can be used individually or combined with other Smart Probes to create measuring solutions for most HVAC/R applications. Great for setup and diagnostics of large and small HVAC/R systems!

The testo 605i works on smart devices with either Android or Apple operating systems.


The testo **Smart Probes App** is a powerful and easy-to-use tool. It allows you to remotely read measurements from up to six (6) Smart Probes and easily document/report the results. Automatic calculations make it a snap!

All measurement data is displayed as instrument readings, tables, or graphs. The measurements can be quickly saved as PDF or Excel files. The App creates custom reports which can be saved and/or shared by email. All your data can be stored and retrieved saving you hours of time consuming paperwork!

# Technical data/accessories

**testo 605i**


testo 605i, Bluetooth thermo-hygrometer with App, incl. 3 AAA batteries and certificate of calibration



Order no. 0560 2605 03

**Testo Smart Probes App**

The Testo **Smart Probes App** combines the power of your smart phone/tablet with the accurate measurements of your Smart Probes. The operation and display of the instruments are communicated via Bluetooth to the App on your smart phone or tablet. The **Smart Probes App** uses the measurements to create custom reports (including added photos and comments). Information and reports can be saved as files and/or sent by e-mail. For Apple iOS and Android.



Sensor type	Humidity – capacitive
Measuring range	0 to 100% RH
Accuracy	±3.0 %RH (10 to 35 %RH) ±2.0 %RH (35 to 65 %RH) ±3.0 %RH (65 to 90 %RH) ±5 %RH (< 10 %RH or > 90 %RH) (at 77 °F)
Resolution	0.1% RH

Sensor type	NTC
Measuring range	-4 to 140 °F
Accuracy	±1.4 °F (-4 to 32 °F) ±0.9 °F (32 to 140 °F)
Resolution	0.1 °F

General technical data	
Compatibility	requires iOS 8.3 (or later) / Android 4.3 (or later) requires mobile device with Bluetooth 4.0
Storage temperature	-4 to 140 °F
Operating temperature	-4 to 122 °F
Battery type	3 AAA Batteries (incl.)
Battery life	150 hrs
Dimensions	8.6 x 1.2 x 1.0 in Probe shaft: 2.9 in (L), 0.5 (dia.)
Warranty	2 years
Measuring Units	°F, °C, %rF / %RH, °Ftd, °Ctd, wetbulb °F, wetbulb °C

**Also Available:**



AC & Refrigeration Kit:  
0563 0002 20



AC/R Test & Load Kit:  
0563 0009

**Accessories**

**Order no.**

testo Smart Case (Refrigeration) for the storage and transport of all testo Smart Probes	0516 0283
--	-----------

testo 605i data sheet ver 1.0 | Subject to change without notice | Not responsible for typographical errors.