WATER METERS

GPI PROVIDES WATER METER OPTIONS

GPI offers three different meters for water. Choose the **TM Meters** when you have a high-volume, water application.

SPECS	Tenter and the second	B CALIBRATE DISPLAY WINTER WINTER BILLION	
		"Look for the silver label!"	"Look for the blue label!"
MODEL	01N SERIES	03N SERIES	TM SERIES
PART NUMBER	113255-4 (1 in. NPT, gallons) 113255-5 (1 in. NPT, litres) 113255-6 (1 in. ISO, litres)	113900-9510 0.3-3 GPM 113900-9511 3-50 GPM	TM050 1/2 in. TM075 3/4 in. TM100 1 in. TM150 1-1/2 in. TM200 2 in. TM300 3 in. TM400 4 in.
CONSTRUCTION & TYPE	Nylon - Electronic Digital	Nylon - Electronic Digital	Schd. 80 PVC - Turbine
DISPLAY	4-digit LCD	6-digit LCD	6-digit LCD
GALLON OR LITRE MODEL	Order gallon or litre model.	Comes with gallon & litre display.	Comes with gallon & litre display.
FLOW RANGE	3-30 GPM (10-100 LPM)	Depends on the model. (see above)	1/2 in. 1-10 GPM 3/4 in. 2-20 GPM 1 in. 5-50 GPM 1-1/2 in. 10-100 GPM 2 in. 20-200 GPM 3 in. 40-400 GPM 4 in. 60-600 GPM
POWERED BY	Two alkaline AAA batteries (Average 5-year use)†	Two lithium batteries (Average 5-year use)†	Two lithium batteries (Average 5-year use)†
ACCURACY	$^{+}/_{-}$ 2.5% of reading	+/_ 1.5% of reading	+/- 3.0% of reading
PRESSURE RATING	150 PSI	150 PSI	225 PSI
FIELD CALIBRATION	No	Yes	Yes
INLET/OUTLET SIZES	1 in. NPT or ISO (Female)	1 in. NPT	Specify either Spigot or NPT model. Flange available on 3 and 4 in. models only.
UNIQUE FEATURE	Weighs just 12 oz. to mount at the hose end.	Provides both Batch (single use) and Cumulative totals.	Sturdy construction with easy access to internal parts.
USE WITH	Water	Water or mild chemicals	Water or mild chemicals
APPROVALS	CE on export model only.	CE, FM, U.L. Classified to Cana- dian Stds. & ATEX ANNEX VIII	CE
WARRANTY	1 Year	1 Year	1 Year
34			

† Battery life will vary depending on usage

Find Quality Products Online at:

www.GlobalTestSupply.com

sales@GlobalTestSupply.com