


Non-contact, high-accuracy measurement system Laser Scan Micrometer LSM-6902H



Best-in-Class Repeatability of $\pm 0.045\mu\text{m}$



The laser beam shown is simulated for the purpose of illustration.



Sensor Systems



Non-contact, high-accuracy measurement system

Laser Scan Micrometer LSM-6902H



Features

- The best repeatability available in the 25mm/1" class.
- The ultra-precise scanning motor enables the highest measurement accuracy.
- Thanks to excellent linearity, an accuracy of $\pm 0.5\mu\text{m}$ over the entire measuring range and a higher accuracy of $\pm(0.3+0.1\Delta D)\mu\text{m}$ over a narrow range are guaranteed.
- An excellent option for measuring pin gages or plug gages.


Specifications

Set Order No.	544-499A(mm/inch)			
Applicable standards	IEC · FDA			
Measuring unit		Display unit		
Measuring range	0.1 to 25mm (0.004 - 1.0 in)	Display	16-digit plus 11-digit fluorescent display, and guide message LED	
Resolution	0.01 to 10 μm (selectable) (0.000001 - 0.0005 in)	Segment	1 to 7 (1 to 3, transparent) or 1 to 255 edges	
Repeatability*1	Whole range	$\pm 0.045\mu\text{m}$ (± 0.0000018 in) ($\phi 25\text{mm}$)	Averaging times	Arithmetic average: 1 to 2048 scans. Moving average: 32 to 2048 scans.
	Narrow range	$\pm 0.03\mu\text{m}$ (± 0.0000012 in) ($\phi 10\text{mm}$)	Judgment	Selection from "target value + tolerance", "lower tolerance + upper tolerance", or "7 classes multimit tolerance zone".
Accuracy*2 (20°C)	Whole range	$\pm 0.5\mu\text{m}$ (± 0.000020 in)	Measurement mode	Standby, Single measurement, Continuous measurement
	Narrow range	$\pm(0.3+0.1\Delta D)$ [D:mm] μm $\pm(0.00012+0.0001\Delta D)$ [D:inch]*5	Statistical analysis	Maximum, Minimum, Max-Min, Average, Dispersion, (S.D)
Movement error*3	$\pm 0.5\mu\text{m}$ (± 0.000020 ")	External dimensions	335(W) \times 134(H) \times 250(D)mm	
Measuring region*4	$\pm 1.5\text{mm}\times 25\text{mm}$ ($\pm 0.006\times 1.0$ in)	Power supply	100 to 240VAC $\pm 10\%$ 35W 50/60Hz	
Scanning rate	1600 scans/s	Standard output	RS-232C, Analog I/O	
Laser wavelength	650nm (visible)	Optional output	Digimatic code output unit (2-ch), 2nd I/O analog I/F, BCD I/F	
Laser scanning speed	112m/s	Operating environment	0 to 40°C, RH 35 to 85% (non-condensing)	
Operating environment	Temperature	0 to 40°C	Others	Nominal setting, sample setting, suppression of unnecessary digits, transparent object measurement, automatic measurement in edge mode, output timer, abnormal data elimination, SHL change, group judgment, simultaneous measurement, statistical processing, mastering, buzzer function, automatic workpiece detection (dimension/position), zero-set/offset Note: In the case of dual measuring-unit connection, extra-fine line measurement and some of the communication commands are not available.
	Humidity	RH 35 to 85% (non-condensing)		



*1: At the 2σ level in the case where $\phi 25\text{mm}$ and $\phi 10\text{mm}$ diameters are measured using a measurement time of 1.28 seconds (2048 scans on average) *2: The value at the center of the measuring range
*3: The additional error (in outside diameter) caused by workpiece movement within the measuring envelope during the measuring cycle *4: Length along optical axis \times Scanning length (Measuring range)
*5: ΔD is the difference in outside diameter between the master gage and workpiece.

Dimensions



- Coordinate Measuring Machines
- Vision Measuring Systems
- Form Measurement
- Optical Measuring
- Sensor Systems
- Test Equipment and Seismometers
- Digital Scale and DRO Systems
- Small Tool Instruments and Data Management

Note: All information regarding our products, and in particular the illustrations, drawings, dimensional and performance data contained in this printed matter as well as other technical data are to be regarded as approximate average values. We therefore reserve the right to make changes to the corresponding designs. The stated standards, similar technical regulations, descriptions and illustrations of the products were valid at the time of printing. In addition, the latest applicable version of our General Trading Conditions will apply. Only quotations submitted by ourselves may be regarded as definitive. Specifications are subject to change without notice.

Mitutoyo products are subject to US Export Administration Regulations (EAR). Re-export or relocation of our products may require prior approval by an appropriate governing authority.

Trademarks and Registrations

Designations used by companies to distinguish their products are often claimed as trademarks. In all instances where Mitutoyo is a registered trademark, it is used with the permission of the trademark owner.