

ARBITRARY WAVEFORM / DDS FUNCTION GENERATOR



DFG-1010 & DFG-1020



AFG-1010 & AFG-1020

Features

- Direct Digital Synthesis technology (DDS)
- 3.5-inch TFT LCD display
- Sampling rate 100Ms/s, vertical resolution 8 bit & waveform length 1Kpts
- Arbitrary waveform functions, up to 8 sets of users' defined waveforms
- 40 sets panel setting save & recall
- Min.1mV (50Ω) waveform output with good stability
- 0.1% pulse duty cycle resolution
- FM, FSK, ASK, and PSK modulations
- Over voltage & current protection, short circuit & reverse voltage protection
- Numeric keyboard and rotary dial for data input
- Built-in 100MHz Frequency Counter
- RS232 interface

Technical Specification

Model	DFG-1010	DFG-1020	AFG-1010	AFG-1020		
Frequency (Output A)						
Frequency range (Sine Wave)	40mHz~10MHz	40mHz~20MHz	40mHz~10MHz	40mHz~20MHz		
	Other Waveforms: 40mHz~1MHz					
Resolution & Accuracy						
	40mHz, ± (50ppm + 40mHz)					
Waveform (Output A)						
Waveform types	32 types waveforms, including Sine, Square, Pulse		40 types waveforms, including Sine, Square, Pulse and 8 sets of arbitrary waveforms			
Waveform length	1024 points					
Vertical resolution	8 bits					
Sampling rate	100MSa/s					
Sine harmonic distortion	≥40dBc (<1MHz), ≥35dBc (1MHz~20MHz)					

Find Quality Products Online at:

www.GlobalTestSupply.com

sales@GlobalTestSupply.com

Amplitude (Output A)	
Amplitude range	2mVpp~20Vpp, 40MHz~10MHz (high impedance)
Resolution	20mVpp (amplitude>2Vpp), 2mVpp (amplitude<2Vpp)
Accuracy	± (1% +2 mVrms) (high impedance, RMS, frequency 1kHz)
Stability	±0.5% / 3 hours
Flatness	±5% (frequency of 10MHz or below), ±10% (frequency above 10MHz)
Output impedance	50Ω
Offset (Output A)	
Offset range	±10V (high impedance, attenuation 0 dB)
Resolution & Accuracy	20mVdc, ±(1% + 20mVdc)
Sweep (Output A)	
Linear sweep or frequency sweep	
Sweep range	Free to set starting point and end point
Sweep step	Higher than any figure of the resolution
Sweep rate	10ms~60ms/step
Sweep mode	Linear, Log Up or Log Down, Single
Frequency Modulation (FM) (Output A)	
Carrier signal	Output A waveforms
Modulating signal & deviation	Output B signal or External signal, 0%~20%
Burst (Output A)	
Burst counts & Mode	1~65000 cycles / Internal, External, Single
FSK, ASK, PSK (Output A)	
FSK	Free to set carrier waveform frequency and hopping frequency
ASK	Free to set carrier waveform amplitude and hopping amplitude
PSK	Hopping phase: 0~360°, Max. resolution: 1°
Alternative rate	10ms~60s
Frequency (Output B)	
Frequency range (Sine Wave)	40mHz~1MHz Other Waveforms: 10mHz~100KHz
Resolution & Accuracy	10mHz, ± (1x10 -5+10 mHz)
Waveform (Output B)	
Waveform types	32 types waveforms, including Sine, Square, Pulse
	40 types waveforms, including Sine, Square, Pulse and 8 sets of arbitrary waveforms
Waveform length	1024 points
Sampling range	12.5Ms a/s
Amplitude resolution	8 bits
Square wave duty cycle	1%~99%
Amplitude (Output B)	
Range	50mVpp~20Vpp (high impedance)
Resolution & Impedance	20mVpp / 50Ω
Burst (Output B)	
Burst count & mode	1~65000 cycles / Internal, External, Single
TTL output	
Waveform characteristics	Square wave, rise/fall time ≤20ns
Frequency characteristics	40mHz~1MHz
Amplitude characteristics	TTL and CMOS compatible, low<0.3V, high>4V
Frequency counter	
Frequency range	1Hz~100MHz
Input signal amplitude	100mVpp~20Vpp
General	
Power source &	110V/220V AC, (1±10%), 50Hz (1±5%) / <30V
Environmental	Temperature: 0~40°C, humidity: <80%
Dimension & Weight	365*260*110mm, 3KG