



Xtended Life Digital Combustion & System Analyzers



C155 & C157

- Measures CO2, CO, Ambient CO, Differential temperature, Differential pressure
- Calculate: O2, Gross/net efficiency, Excess air, CO air free
- Worklight
- 4 line backlit LCD display
- 179 memory positions
- User customizable parameters view
- Individual report printouts
- Unique DMM style rotary selector
- Protective boot with integral magnet
- Real time clock
- CO readings to 1 ppm
- Infrared printer port
- 5-Year limited warranty (includes sensors)

C157 Adds:

- Measures NO
- Calculates NOx

Applications

Confirm set up parameters (to manufacturers specifications)

Verify proper combustion, equipment efficiency and integrity

Analyze combustion gas makeup and stack gases

Set gas pressures

Measure temperatures for live fire of gases, temperature rise and differential drops across coils, inlet and superheat readings

Perform pressure test for drops across coils, gas pressures, limit switches, building pressures and zone pressures

Document equipment performance before and after servicing tests to show compliance





Includes

Analyzer	C155 Kit Options				C157 Kit Options			
	C155	C155KIT	C155BTKIT	C155OILKIT	C157	C157KIT	C157BTKIT	C157OILKIT
UEi Part Number								
Kit Type	A. Analyzer Only	B. Combustion Kit	B. Combustion Kit	C. Oil Service Kit	A. Analyzer Only	B. Combustion Kit	B. Combustion Kit	C. Oil Service Kit
UPC Code	05353350585	05353350587	05353350683	05353350589	05353350586	05353350588	05353350771	05353350590
Combustion Analyzer	X	X	X	X	X	X	X	X
12" Flue Probe w/ 10' Hose	X	X	X	X	X	X	X	X
Inlet tube/Probe connector	X	X	X	X	X	X	X	X
Particle Filter (spare)		X	X	X		X	X	X
AC Adapter		X	X	X		X	X	X
K-type Temperature Probes (2)		X	X	X		X	X	X
Owners Manual		X	X	X		X	X	X
Hard Carrying Case	X	X	X	X	X	X	X	X
Infrared Thermal Printer		X		X		X		X
Paper Roll (spare)		X	X	X		X	X	X
Training DVD		X	X	X		X	X	X
Smoke Pump Tester				X				X
NOx Sensor pre-installed					X	X	X	X
Installed Bluetooth Module			X				X	

Specifications

Temperature

Flue Temp Range	20~2400°F (-29~1315°C)
Inlet Temperature (probe - T2)	20~2400°F (-29~1315°C)
Inlet Temperature (ambient)	32~112°F (0~50°C)
Net Temperature (ΔT)**	20~2400°F (-29~1315°C)
Resolution	0.1°C/F
Flue (T1, Inlet T2 & ΔT) Accuracy	±(0.3% rdg +3.6°F(2°C))
Inlet Temperature Accuracy	±(0.3% rdg +1.8°F(1°C))

Gas

Oxygen	0~21%**
O2 resolution / accuracy	0.1% / ±(0.3% absolute)
Carbon Monoxide (CO)	0~2000 ppm (4000 max 15 min)*
CO resolution / accuracy	1 ppm / ±10 ppm<100ppm, ±5% rdg>100ppm
Carbon Dioxide (CO2)	0~20%*
CO2 resolution / accuracy	0.1% / (0.3% absolute)
Efficiency**	0~99.9%**
Efficiency resolution/accuracy	0.1% / ±3%
Excess Air**	0~250%**
Excess Air resolution/accuracy	0.1% / ±3%
CO/CO2 ratio**	0~0.999
CO/CO2 resolution/accuracy	0.001 / ±5% rdg
Nitric Oxide (NO1)***	0~100 ppm
NO1 resolution/accuracy***	±2 ppm <30ppm, ±5ppm <100ppm

Pressure

Range	Accuracy
±0.08" wc (±0.2mBar)	2±0.002" wc (±0.005mBar)
±0.4" wc (±1mBar)	±0.01" wc (±0.03mBar)
±32" wc (±80mBar)	±3% rdg

Resolution	0.001" wc < 9.999" wc
	0.01" wc > 10.00" wc
	0.001mBar < 24.999mBar
	0.01mBar > 25 mBar

* Measured at STP (standard temperature and pressure)

** Calculated value

*** NO1 sensor installed on C157. Available as an upgrade for C155.

† Gas Zero (Fresh Air Zero) - Is a reset procedure to maintain accurate readings from the EOS sensor. This procedure compensates for any change in ambient conditions that may impact the readings.

Downloads



Manual



Quick Start Guide



Data Sheet

H85-577



Sell Sheet

H85-580



Made in UK



Made in UK