



MODEL	B ATTERY OPERATED	NOMINAL STEADY-STATE UV-A INTENSITY at 15 in (38 cm) <b>①</b>	<b>UV-A COVERAGE AREA</b> at 15 in (38 cm) at minimum 1,000 μW/cm²	VISIBLE LIGHT MEASUREMENT
CLA-100		5,700 μW/cm <sup>2</sup>	6 in (15.25 cm)	>350 foot-candle
CLA-100Z	•	5,700 μW/cm <sup>2</sup>	6 in (15.25 cm)	>350 foot-candle

⊕ UV-A intensity reading taken with the Spectroline® NDT AccuMAX™ Series meter, and is factory set to the value shown.

$\epsilon$	UK

	CLA-100	CLA-100Z
Light Source:	2 UV-A LED'S & 1 White LED	2 UV-A LED'S & 1 White LED
Lamp Style:	Corded lamp	Cordless lamp
Lamphead Diameter:	4.4 in (11.18 cm)	4.4 in (11.18 cm)
Length:	6.7 in (17 cm)	6.7 in (17 cm)
Width:	3.4 in ( 8.6 cm)	3.4 in ( 8.6 cm)
Height:	7.45 in (18.9 cm)	7.45 in ( 18.9 cm)
Weight:	1.76 Lb (0.8 Kg)	2.05 Lb (930 g) (with internal battery)
Power Requirements:	90 - 270 VAC, 50 TO 60 Hz	90 - 270 VAC, 50 TO 60 Hz
Run Time:	-	7 to 8 hours (continuous)
Charge Time:	-	2 hours


## CLA-100 & CLA-100Z


## **Classic Series Dual Function LED Inspection Lamp Kit**


Comes complete with Classic Series Dual Function LED Inspection Lamp with lanyard, Smart Charger Power Supply (CLA-100Z only), AC Cord set, UV Absorbing Spectacles, Carrying Case For Spectacles, Protective Carrying Case.



## **UV-A** Beam Profiles







SPECTRO-UV

DISTRIBUTED BY:

NDT 3/23 A10252022-1 PRINTED IN USA