



# FLIR ONE® EDGE SERIES

Thermal cameras with wireless connectivity for iOS® and Android™ smart devices



### Key Features:

- Wirelessly connects to your smart device for convenient inspections
- Unrivaled thermal image clarity with MSX® (Multi-Spectral Dynamic Imaging)
- Use the FLIR ONE app for efficient thermal analysis, and seamlessly connect to the FLIR Ignite™ cloud solution

### Main Applications:

- Identifying and locating moisture intrusion and insulation deficiencies
- Diagnosing issues in HVAC/R inspections
- Identifying abnormalities in electrical and mechanical components

## SPECIFICATIONS

	FLIR ONE Edge	FLIR ONE Edge Pro
Thermal resolution	80 × 60 (4,800 pixels)	160 × 120 (19,200 pixels)
Object temperature range(s)	-20°C to 120°C (-4°F to 248°F)	-20°C to 120°C (-4°F to 248°F) 0°C to 400°C (32°F to 752°F)
VividIR image enhancement	No	Yes
Image presentation modes	MSX, infrared image, visual image	
Live measurement analysis	Hottest, coldest, and 3 adjustable spots	
Android & iOS compatibility	Yes, compatible with both iOS and Android devices	
Wireless remote operation	Yes (up to 5 m from smart device)	
<b>General Features</b>		
Device compatibility	iOS (version 15 and later) or Android (version 11 and later) smartphones and tablets	
IP rating	IP54	
Drop tested	Drop from 2 m (6.56 ft)	
FLIR software compatibility	FLIR ONE app, FLIR Ignite, FLIR Thermal Studio	
SDK available for app development	Yes	
Thermal sensitivity	70 mK	
Certifications	RoHS, CE/FCC, CEC-BC, EN62133, UL1642, WEEE 2012/19/EU	
Operating temperature	-10°C to 50°C (14°F to 122°F), battery charging 0°C to 45°C (32°F to 113°F)	
Storage temperature	-40°C to 70°C (-40°F to 158°F)	
Size (w × h × d)	35 mm × 37.5 mm × 149 mm (1.4 in × 1.5 in × 5.9 in)	
Weight (incl. battery)	153 g (5.4 oz)	
Clip span	130 mm (min) / 195 mm (max)	

	FLIR ONE Edge	FLIR ONE Edge Pro
<b>Optical Data</b>		
Spectral range	8 μm to 14 μm	
Visual resolution	640 × 480	
HFOV / VFOV	54° ±1° / 42° ±1°	
Frame rate	8.7 Hz	
Focus	Fixed 30 cm – infinity	
<b>Measurement</b>		
Accuracy	±3°C (5.4°F) or ±5%. Applicable 60 sec after start-up when the unit is within 15°C to 35°C (59°F to 95°F) and the scene is within 5°C to 120°C (41°F to 248°F)	
Emissivity correction	Matte, Semi-Matte, Semi-Glossy, Glossy	
Measurement correction	Emissivity, Reflected apparent temperature (22°C / 72°F)	
Shutter	Automatic/Manual	
<b>Power</b>		
Battery life	2 h 30 min	
Battery charge time	60–90 min for fully charged. 15 min charging, from empty battery, gives 40 min operating time	
<b>Interfaces</b>		
Wi-Fi	802.11 a/b/g/n	
Bluetooth	Uses Bluetooth to set up the peer-to-peer Wi-Fi network that the camera creates to connect to the mobile device	
Charging	Female USB-C (5V/1A)	
Remote connection	Via Wi-Fi	

Specifications subject to change.

This product is subject to United States export regulations and may require US authorization prior to export, reexport, or transfer to non-US persons or parties. Diversion contrary to US law is prohibited.

For assistance with confirming the Jurisdiction & Classification of Teledyne FLIR, LLC products, please contact. ©2023 Teledyne FLIR, LLC. All rights reserved.

Revised 06/27/23  
FLIR ONE Edge Series\_Datasheet-LTR 23-0403-INS



# FLIR ONE® EDGE SERIES

Thermal Cameras with wireless connectivity for iOS® and Android™ smart devices

## SPECIFICATIONS, CONT.

	FLIR ONE Edge	FLIR ONE Edge Pro
<b>App</b>		
Video and image capture	Yes	
File formats	Radiometric JPG, MPEG-4 (file format MOV (iOS), MP4 (Android))	
Spot measurements	Hottest, Coldest, and 3 spot measurement	
Adjustable MSX distance	0.3 m – infinity	
Visual battery indicator	0% to 100%	
<b>Radio</b>		
Wi-Fi	<ul style="list-style-type: none"><li>• Standard: 802.11 a/ac/b/g/n</li><li>• Frequency range:<ul style="list-style-type: none"><li>- 2401–2473 MHz</li><li>- 5150–5250 MHz</li></ul></li><li>• Max. output power: 15 dBm</li></ul>	
Bluetooth	<ul style="list-style-type: none"><li>• Frequency range:<ul style="list-style-type: none"><li>- 2400–2484 MHz</li></ul></li><li>• Max. output power: 10 dBm</li></ul>	

Apple Store FLIR Apps



Google Play Store FLIR Apps



Specifications subject to change.

This product is subject to United States export regulations and may require US authorization prior to export, reexport, or transfer to non-US persons or parties. Diversion contrary to US law is prohibited.

For assistance with confirming the Jurisdiction & Classification of Teledyne FLIR, LLC products, please contact. ©2023 Teledyne FLIR, LLC. All rights reserved.

Revised 06/27/23  
FLIR ONE Edge Series\_Datasheet-LTR 23-0403-INS