

TEE HANDLE COCK



◀ **MODEL A10**

In polished brass (suitable for pressure to 125 PSI hydraulic) Specify Type **A10** 1/4" NPT female connections. **A11** 1/4" NPT male x female

HEAVY DUTY TEE HANDLE



◀ **MODEL A10E**

In polished brass for pressures to 200 psi hydraulic, 1/4" NPT female connections with hex shoulders.

LEVER HANDLE COCK



◀ **MODEL A12**

1/4" NPT female connections. In polished brass suitable for pressure to 200 psi hydraulic. Specify Type **A12**.

SIPHON




◀ **MODEL AO31**

Schedule 40 Steel (for max. 500 PSI and 400°F) Specify Type **AO31**. 1/4" NPT. Brass (for max. 250 PSI and 400°F specify type **AO3B**).

SNUBBER-FILTER TYPE

3/4" Hexagon, 1/4" NPT

Porous Stainless Steel Filter Disc



◀ **MODEL WG41
WG42**

Brass with 1/8" thick micro-metallic stainless steel filter (max pressure 1500 psi) Available 1/4" NPT only. Specify **WG41** for air. Specify **WG42** for water or light oil. **WS41/WS42** Stainless steel body instead of brass.

BAR STOCK NEEDLE



◀ **MODEL BBV4**

Brass, 1/4" NPT female connections only. Suitable for 600 psi at 300° F maximum; for water, oil or gas service.